



## Technical Details

EXTERNAL SHELL: ABS  
 INTERNAL SHELL: HD Polystyrene  
 HEADBAND: Soft PA Nylon headband  
 (fixed to the external shell without metal rivets)  
 SIZE: Universal-adjustable from 51 to 62 cm  
 STANDARD: EN 14052

 450 g  -10°C / +50°C



WHE00007.201  
WHITE



WHE00007.202  
YELLOW



WHE00007.204  
RED

## Technology



AIR

**VENTILATION:** Maximum ventilation thanks to the ten air intakes. The air intakes and the internal outflow channels guarantee effective breathability.



CLIP

**LAMP CLIPS:** Helmet equipped with strong nylon external lamp carrying clips, made of high intensity resin and frontal antislid insert that are compatible with all headlamps with elastic bands on the market.



CHINSTRAP  
EN 14052

**CHINSTRAP EN 14052:** Four point chinstrap. The safety release system allows quick fastening and opening of the locking mechanism in conformity with EN 14052. Provided with lateral divider for adjusting the length of the straps.



RING TO HOOK

**RING TO HOOK:** Fitted with a special loop on the chinstrap which allows the helmet to be connected to the harness.



2DRY

**2DRY:** This high-tech and maximum comfort fabric dries very quickly, encouraging the expansion and dispersion of moisture to the outside and leaving a pleasant feeling of freshness.



**MICROMETRICAL ADJUSTMENT:** The micrometrical size regulation mechanism positioned at the rear of the helmet provides quick and precise adjustment, even when wearing gloves.



VISOR






**VISOR ATTACHMENT:** Provided with attachment for fitting visors.




EARMUFFS

**EARMUFFS FITTING:** Provided with bayonet socket adapter for earmuffs. Compatible with KASK earmuffs.

## Performances

PROTECTION AGAINST TOP IMPACTS	 5 Kg from 2 m 100 J
PROTECTION AGAINST SIDE, FRONT AND REAR IMPACTS	 5 Kg from 1 m 50 J
PROTECTION AGAINST THE PENETRATION OF OBJECTS	 TOP: 1 Kg from 2,5 m 25 J LAT: 1 Kg from 2 m 20 J
CHIN STRAP RELEASE > 15 kg <25 kg	
RETENTION SYSTEM EFFECTIVENESS	



 Standard requirements

## Additional Information



### GUARANTEE

3 years starting from the purchasing date.

### SHELF LIFE

10 years starting from the production date (production date is printed on a label contained on the inside of the helmet).

Inspect the helmet regularly to check for any damage! Cuts, abrasions, deformation or changes in colour represent important elements for checking the helmet status.

### CLEANING

Clean the helmet only with water, neutral pH soap and a soft, clean cloth. The inner lining should be washed by hand in cold water or in the washing machine (max 30°C - 85°F). Do not use chemical detergent or solvent.

### STORAGE

When not in use the helmet should be stored away from direct sunlight or source of heat.

### ADHESIVE APPLICATION

Do not apply adhesives, solvents, stickers or paint that do not comply with the manufacturer's specifications. Any alteration or intervention not provided for may impair its protective function.

## Accessories



WV100018  
Visor V2 Plus



WV100003  
Visor FULL FACE



WV100006  
Mesh visor



WAC00003  
Adapter for earmuffs



WPA00002  
Inner padding



WAC00008  
Visor carrier 30 mm attachment



WV100005  
Mesh visor carrier



WHP00004/5/6  
Earmuffs



WAC00026  
Helmet bag



WPA00007  
Winter padding



WAC00020  
Neck Shade



WAC00024  
Neck Shade HI VIZ